

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Tripp Lite](#)
[SUPER-7](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Tripp Lite

1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Protect It! 7-Outlet Surge Protector, 7-ft. Cord, 2160 Joules, White Housing

MODEL NUMBER: **SUPER7**



Highlights

- 7 outlets/7 ft. cord
- 2160 joule rating
- \$75,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

Package Includes

- Super 7 Surge Suppressor
- Instruction manual with warranty information

Description

The SUPER7 Surge Suppressor from Tripp Lite has 7 outlets, a 7-ft. cord with a space-saving right-angle plug, and diagnostic LEDs. The unit has a surge suppression rating of 2160 joules to handle the strongest surges. \$75,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

Features

- 7 outlets
- 7-ft. cord with space-saving right-angle plug
- Surge suppression rating: 2160 joules
- EMI/RFI noise filtering
- Can accommodate up to 3 transformers without blocking remaining outlets
- \$75,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only) covers connected equipment
- Diagnostic LEDs indicate protection present & ground present
- Keyhole supports for wall mounting
- Automatic shutoff cuts power to outlets when the protection circuit has been compromised

Specifications

| OUTPUT | |
|---------------------------|--|
| Frequency Compatibility | 50 / 60 Hz |
| Output Receptacles | (7) 5-15R |
| Output (Watts) | 1800 |
| Circuit Breaker (amps) | 15 |
| Transformer Accommodation | Supports 3 large transformer plug accessories without covering remaining outlets, accepts up to 5 transformers total |



Tripp Lite
 1111 W. 35th Street
 Chicago, IL 60609 USA
 Telephone: 773.869.1234
 www.tripplite.com

| | |
|--|---|
| Outlet Orientation | Single row of 5, plus 2 side mounted outlets |
| Right-Angle Outlets | No |
| INPUT | |
| Nominal Input Voltage(s) Supported | 120V AC |
| Recommended Electrical Service | 120V (110-125V) |
| Input Connection Type | NEMA 5-15P |
| Input Cord Length (ft.) | 7 |
| Input Cord Length (m) | 2.1 |
| Input Cord Gauge Type | 14 gauge, SJT |
| Voltage Compatibility (VAC) | 120 |
| Maximum Surge Amps | 144000 |
| Right-Angle Plug | Yes |
| USER INTERFACE, ALERTS & CONTROLS | |
| Switches | Two position on/off power switch |
| Diagnostic LED Details | Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status |
| SURGE / NOISE SUPPRESSION | |
| AC Suppression Joule Rating | 2160 |
| AC Suppression Response Time | < 1 ns |
| Protection Modes | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression |
| Clamping Voltage (RMS) | 150 |
| UL1449 Let Through Rating | 330 L-G, 400 L-N, 400 N-G |
| EMI / RFI Filtering | Up to 20 dB |
| DATALINE SURGE SUPPRESSION | |
| Telephone/DSL Protection | No |
| Cable (Coax) Protection | No |
| Network (Ethernet) Protection | No |
| PHYSICAL | |
| Shipping Dimensions (hwd / in.) | 12.40 x 5.90 x 1.77 |
| Shipping Dimensions (hwd / cm) | 31.50 x 14.99 x 4.50 |
| Shipping Weight (lbs.) | 1.56 |
| Shipping Weight (kg) | 0.71 |



Tripp Lite
 1111 W. 35th Street
 Chicago, IL 60609 USA
 Telephone: 773.869.1234
 www.tripplite.com

| | |
|--|---|
| Unit Dimensions (hwd / in.) | 1.54 x 2.72 x 10.30 |
| Unit Dimensions (hwd / cm) | 3.91 x 6.91 x 26.16 |
| Unit Weight (lbs.) | 1.39 |
| Unit Weight (kg) | 0.63 |
| Material of Construction | Plastic |
| Integrated Keyhole Mounting Tabs | Keyhole mounting tabs enable wall mounting |
| Housing Color | Light gray |
| Receptacle Color | Light Gray |
| Color (AC Line Cord) | Light Gray |
| Outlets Measurement (Center to Center) | Between Standard Outlets = 29mm; Between Transformer Outlets = 48mm |
| Keyhole Slot Mounting Measurement (Center to Center) | Distance Between Slots = 78mm; Distance Between Slot Height = 24mm |
| CERTIFICATIONS | |
| UL1449 3rd Edition (AC Suppression) | UL1449 3RD EDITION |
| UL1363 (Power Tap) | UL1363 |
| cUL / CSA (Canada) | cUL |
| Approvals | Exceeds IEEE 587 category A&B specifications |
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$75,000 Ultimate Lifetime Insurance |

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <http://www.tripplite.com/products/product-certification-agencies>