

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[International Rectifier \(Infineon Technologies Americas Corp.\)](#)  
[IRG4PH20KPBF](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

International  
**IR** Rectifier

PD - 95624

## IRG4PH20KPbF

### INSULATED GATE BIPOLAR TRANSISTOR


Short Circuit Rated  
UltraFast IGBT

#### Features


- High short circuit rating optimized for motor control,  $t_{sc} = 10\mu s$ ,  $V_{CC} = 720V$ ,  $T_J = 125^\circ C$ ,  $V_{GE} = 15V$
- Combines low conduction losses with high switching speed
- Latest generation design provides tighter parameter distribution and higher efficiency than previous generations
- Lead-Free

#### Benefits

- As a Freewheeling Diode we recommend our HEXFRED™ ultrafast, ultrasoft recovery diodes for minimum EMI / Noise and switching losses in the Diode and IGBT
- Latest generation 4 IGBT's offer highest power density motor controls possible



|                                 |
|---------------------------------|
| $V_{CES} = 1200V$               |
| $V_{CE(on) typ.} = 3.17V$       |
| @ $V_{GE} = 15V$ , $I_C = 5.0A$ |



### Absolute Maximum Ratings

|                           | Parameter                          | Max.                              | Units      |
|---------------------------|------------------------------------|-----------------------------------|------------|
| $V_{CES}$                 | Collector-to-Emitter Voltage       | 1200                              | V          |
| $I_C @ T_C = 25^\circ C$  | Continuous Collector Current       | 11                                | A          |
| $I_C @ T_C = 100^\circ C$ | Continuous Collector Current       | 5.0                               |            |
| $I_{CM}$                  | Pulsed Collector Current ①         | 22                                |            |
| $I_{LM}$                  | Clamped Inductive Load Current ②   | 22                                |            |
| $t_{sc}$                  | Short Circuit Withstand Time       | 10                                | $\mu s$    |
| $V_{GE}$                  | Gate-to-Emitter Voltage            | $\pm 20$                          | V          |
| $E_{ARV}$                 | Reverse Voltage Avalanche Energy ③ | 130                               | mJ         |
| $P_D @ T_C = 25^\circ C$  | Maximum Power Dissipation          | 60                                | W          |
| $P_D @ T_C = 100^\circ C$ | Maximum Power Dissipation          | 24                                |            |
| $T_J$                     | Operating Junction and             | -55 to +150                       | $^\circ C$ |
| $T_{STG}$                 | Storage Temperature Range          |                                   |            |
|                           | Soldering Temperature, for 10 sec. | 300 (0.063 in. (1.6mm) from case) |            |
|                           | Mounting torque, 6-32 or M3 screw. | 10 lbf·in (1.1N·m)                |            |

### Thermal Resistance

|                 | Parameter                                 | Typ.     | Max. | Units        |
|-----------------|-------------------------------------------|----------|------|--------------|
| $R_{\theta JC}$ | Junction-to-Case                          | —        | 2.1  | $^\circ C/W$ |
| $R_{\theta CS}$ | Case-to-Sink, Flat, Greased Surface       | 0.24     | —    |              |
| $R_{\theta JA}$ | Junction-to-Ambient, typical socket mount | —        | 40   |              |
| $Wt$            | Weight                                    | 6 (0.21) | —    | g (oz)       |

www.irf.com

8/3/04

# IRG4PH20KPbF

International  
**IR** Rectifier

## Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

|                                 | Parameter                                | Min. | Typ. | Max.      | Units   | Conditions                                             |
|---------------------------------|------------------------------------------|------|------|-----------|---------|--------------------------------------------------------|
| $V_{(BR)CES}$                   | Collector-to-Emitter Breakdown Voltage   | 1200 | —    | —         | V       | $V_{GE} = 0V, I_C = 250\mu A$                          |
| $V_{(BR)ECS}$                   | Emitter-to-Collector Breakdown Voltage ④ | 18   | —    | —         | V       | $V_{GE} = 0V, I_C = 1.0A$                              |
| $\Delta V_{(BR)CES}/\Delta T_J$ | Temperature Coeff. of Breakdown Voltage  | —    | 1.13 | —         | V/°C    | $V_{GE} = 0V, I_C = 2.5mA$                             |
| $V_{CE(ON)}$                    | Collector-to-Emitter Saturation Voltage  | —    | 3.17 | 4.3       | V       | $I_C = 5.0A, V_{GE} = 15V$                             |
|                                 |                                          | —    | 4.04 | —         |         | $I_C = 11A$ See Fig. 2, 5                              |
|                                 |                                          | —    | 2.84 | —         |         | $I_C = 5.0A, T_J = 150^\circ\text{C}$                  |
| $V_{GE(th)}$                    | Gate Threshold Voltage                   | 3.5  | —    | 6.5       |         | $V_{CE} = V_{GE}, I_C = 250\mu A$                      |
| $\Delta V_{GE(th)}/\Delta T_J$  | Temperature Coeff. of Threshold Voltage  | —    | -10  | —         | mV/°C   | $V_{CE} = V_{GE}, I_C = 1mA$                           |
| $g_{fe}$                        | Forward Transconductance ⑤               | 2.3  | 3.5  | —         | S       | $V_{CE} = 100V, I_C = 5.0A$                            |
| $I_{CES}$                       | Zero Gate Voltage Collector Current      | —    | —    | 250       | $\mu A$ | $V_{GE} = 0V, V_{CE} = 1200V$                          |
|                                 |                                          | —    | —    | 2.0       |         | $V_{GE} = 0V, V_{CE} = 10V, T_J = 25^\circ\text{C}$    |
|                                 |                                          | —    | —    | 1000      |         | $V_{GE} = 0V, V_{CE} = 1200V, T_J = 150^\circ\text{C}$ |
| $I_{GES}$                       | Gate-to-Emitter Leakage Current          | —    | —    | $\pm 100$ | nA      | $V_{GE} = \pm 20V$                                     |

## Switching Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)


|              | Parameter                         | Min. | Typ. | Max. | Units   | Conditions                                                                 |
|--------------|-----------------------------------|------|------|------|---------|----------------------------------------------------------------------------|
| $Q_g$        | Total Gate Charge (turn-on)       | —    | 28   | 43   | nC      | $I_C = 5.0A$                                                               |
| $Q_{ge}$     | Gate - Emitter Charge (turn-on)   | —    | 4.4  | 6.6  |         | $V_{CC} = 400V$ See Fig.8                                                  |
| $Q_{gc}$     | Gate - Collector Charge (turn-on) | —    | 12   | 18   |         | $V_{GE} = 15V$                                                             |
| $t_{d(on)}$  | Turn-On Delay Time                | —    | 23   | —    | ns      | $T_J = 25^\circ\text{C}$                                                   |
| $t_r$        | Rise Time                         | —    | 26   | —    |         | $I_C = 5.0A, V_{CC} = 960V$                                                |
| $t_{d(off)}$ | Turn-Off Delay Time               | —    | 93   | 140  |         | $V_{GE} = 15V, R_G = 50\Omega$                                             |
| $t_f$        | Fall Time                         | —    | 270  | 400  |         | Energy losses include "tail" See Fig. 9,10,14                              |
| $E_{on}$     | Turn-On Switching Loss            | —    | 0.45 | —    | mJ      |                                                                            |
| $E_{off}$    | Turn-Off Switching Loss           | —    | 0.44 | —    |         |                                                                            |
| $E_{ts}$     | Total Switching Loss              | —    | 0.89 | 1.2  |         |                                                                            |
| $t_{sc}$     | Short Circuit Withstand Time      | 10   | —    | —    | $\mu s$ | $V_{CC} = 720V, T_J = 125^\circ\text{C}$<br>$V_{GE} = 15V, R_G = 50\Omega$ |
| $t_{d(on)}$  | Turn-On Delay Time                | —    | 23   | —    | ns      | $T_J = 150^\circ\text{C}$                                                  |
| $t_r$        | Rise Time                         | —    | 28   | —    |         | $I_C = 5.0A, V_{CC} = 960$                                                 |
| $t_{d(off)}$ | Turn-Off Delay Time               | —    | 100  | —    |         | $V_{GE} = 15V, R_G = 50\Omega$                                             |
| $t_f$        | Fall Time                         | —    | 620  | —    |         | Energy losses include "tail" See Fig. 10,11,14                             |
| $E_{ts}$     | Total Switching Loss              | —    | 1.7  | —    | mJ      |                                                                            |
| $L_E$        | Internal Emitter Inductance       | —    | 13   | —    | nH      | Measured 5mm from package                                                  |
| $C_{ies}$    | Input Capacitance                 | —    | 435  | —    | pF      | $V_{GE} = 0V$                                                              |
| $C_{oes}$    | Output Capacitance                | —    | 44   | —    |         | $V_{CC} = 30V$ See Fig. 7                                                  |
| $C_{res}$    | Reverse Transfer Capacitance      | —    | 8.3  | —    |         | $f = 1.0MHz$                                                               |

### Notes:


- ① Repetitive rating;  $V_{GE} = 20V$ , pulse width limited by max. junction temperature. ( See fig. 13b )
- ②  $V_{CC} = 80\%(V_{CES}), V_{GE} = 20V, L = 10\mu H, R_G = 50\Omega$ , (See fig. 13a)
- ③ Repetitive rating; pulse width limited by maximum junction temperature.
- ④ Pulse width  $\leq 80\mu s$ ; duty factor  $\leq 0.1\%$ .
- ⑤ Pulse width  $5.0\mu s$ , single shot.

International  
**IR** Rectifier


## IRG4PH20KPbF



**Fig. 1** - Typical Load Current vs. Frequency  
(Load Current =  $I_{RMS}$  of fundamental)




**Fig. 2** - Typical Output Characteristics




**Fig. 3** - Typical Transfer Characteristics

# IRG4PH20KPbF


International  
**IR** Rectifier



**Fig. 4** - Maximum Collector Current vs. Case Temperature




**Fig. 5** - Typical Collector-to-Emitter Voltage vs. Junction Temperature




**Fig. 6** - Maximum Effective Transient Thermal Impedance, Junction-to-Case

International  
**IR** Rectifier


## IRG4PH20KPbF




**Fig. 7** - Typical Capacitance vs. Collector-to-Emitter Voltage



**Fig. 8** - Typical Gate Charge vs. Gate-to-Emitter Voltage




**Fig. 9** - Typical Switching Losses vs. Gate Resistance




**Fig. 10** - Typical Switching Losses vs. Junction Temperature

## IRG4PH20KPbF

International  
**IR** Rectifier




**Fig. 11** - Typical Switching Losses vs. Collector-to-Emitter Current




**Fig. 12** - Turn-Off SOA

International  
**IR** Rectifier


## IRG4PH20KPbF



**Fig. 13a** - Clamped Inductive Load Test Circuit




**Fig. 13b** - Pulsed Collector Current Test Circuit



**Fig. 14a** - Switching Loss Test Circuit

\* Driver same type as D.U.T.,  $V_c = 960V$




**Fig. 14b** - Switching Loss Waveforms

# IRG4PH20KPbF

International  
**IR** Rectifier


## TO-247AC Package Outline

Dimensions are shown in millimeters (inches)



## TO-247AC Part Marking Information

EXAMPLE: THIS IS AN IRFPE30  
WITH ASSEMBLY  
LOT CODE 5657  
ASSEMBLED ON WW 35, 2000  
IN THE ASSEMBLY LINE "H"  
**Note:** "P" in assembly line  
position indicates "Lead-Free"



Data and specifications subject to change without notice.

International  
**IR** Rectifier

**IR WORLD HEADQUARTERS:** 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105  
TAC Fax: (310) 252-7903

Visit us at [www.irf.com](http://www.irf.com) for sales contact information.08/04

[www.irf.com](http://www.irf.com)

Note: For the most current drawings please refer to the IR website at:

<http://www.irf.com/package/>