

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ASSMANN WSW Components](#)

[AK500-OE-11-.5](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

	1	2	3	4	5	6	7																																																																																		
A								A																																																																																	
B								B																																																																																	
C								C																																																																																	
D								D																																																																																	
E								E																																																																																	
F	BLACK WHITE GREEN COPPER CONDUCTOR(N/mm): 40/0.162±0.005 or Substitute PVC INSULATION AVERAGE THICKNESS: 0.38mm ID: 2.10±0.1mm DENIER:1500d PVC JACKET AVERAGE THICKNESS: 0.76mm OD: 6.30 ±0.2mm Material: - SVT 3x18AWG(0.824MM²) VW-1 , 60°C 300V - Jacket Color: Black - E- Green; L- Black; N- White Electrical : 100% Open & Short Testing - Insulation Resistance : 100meg-ohm(Min.) - Voltage : 500V DC / 1 Min.							F																																																																																	
G	<table border="1"> <thead> <tr> <th>Scale</th><th>Free</th><th></th><th></th><th></th><th></th><th>Date</th><th>Name</th><th>Title</th></tr> </thead> <tbody> <tr> <td>TOLERANCE</td><td></td><td></td><td></td><td></td><td></td><td>Drawn</td><td>27.12.11</td><td>Chappell</td></tr> <tr> <td>X.</td><td>±X</td><td></td><td></td><td></td><td></td><td>Approved</td><td>21.06.13</td><td>Groll</td></tr> <tr> <td>X.X</td><td>±X</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr> <td>X.XX</td><td>±X</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr> <td>DIM</td><td>TOL</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr> <td>X.°</td><td>±X°</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr> <td>X.X°</td><td>±X°</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr> <td>Angle</td><td>TOL</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> </tbody> </table> Unit: mm RoHS Compliant ASSMANN WSW components 1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us Power cord - IEC Extension SVT, 18AWG, 60°C, Unshielded, 0.5 meter ASSMANN WSW-No. AK500-OE-11-0.5 Drawing-No. rev01 Replace Sheet 1/1							Scale	Free					Date	Name	Title	TOLERANCE						Drawn	27.12.11	Chappell	X.	±X					Approved	21.06.13	Groll	X.X	±X								X.XX	±X								DIM	TOL								X.°	±X°								X.X°	±X°								Angle	TOL								G
Scale	Free					Date	Name	Title																																																																																	
TOLERANCE						Drawn	27.12.11	Chappell																																																																																	
X.	±X					Approved	21.06.13	Groll																																																																																	
X.X	±X																																																																																								
X.XX	±X																																																																																								
DIM	TOL																																																																																								
X.°	±X°																																																																																								
X.X°	±X°																																																																																								
Angle	TOL																																																																																								
H								H																																																																																	
	1	2	3	4	5	6	7																																																																																		