

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ASSMANN WSW Components](#)

[AK500-OE-11-1](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

	1	2	3	4	5	6	7	
A								A
B								B
C								C
D								D
E								E
F								F
G								G
H								H

Unit: mm

BLACK

WHITE

GREEN

COPPER CONDUCTOR(N/mm):
40/0.162±0.005 or Substitute

PVC INSULATION AVERAGE
THICKNESS: 0.38mm
ID: 2.10±0.1mm

DENIER:1500d

PVC JACKET AVERAGE
THICKNESS: 0.76mm
OD: 6.30 ±0.2mm

Material:
 . SVT 3x18AWG(0.824MM²) VW-1 Unshielded, 60° 300V
 . Jacket Color: Black
 . E- Green; L- Black; N- White

Electrical :
 . 100% Open & Short Testing
 . Insulation Resistance : 100meg-ohm(Min.)
 . Voltage : 500V DC / 1 Min.

Scale	Free					Date	Name	Title
TOLERANCE						Drawn	27.12.11	Chappell
X.	±X					Approved	21.06.13	Groll
X.X	±X							
X.XX	±X							
DIM	TOL							
X.°	±X°							
X.X°	±X°	①	Updated all information	21.06.13	Wilson			
Angle	TOL	Id.	Modification	Date	Name			

1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283
 Toll Free: 1-877-277-6266 • Email: info@assmann.us

Title	
Power cord - IEC Extension SVT, 18AWG, 60°C, Unshielded, 1 meter	
ASSMANN WSW-No. AK500-OE-11-1	
Drawing-No.	rev01
Replace	Sheet 1/1