

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Diodes Incorporated](#)
[BAS7004TA](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

SOT23 SILICON PLANAR DUAL SCHOTTKY BARRIER DIODES

ISSUE 3 - JULY 1995



**BAS70-04
BAS70-05
BAS70-06**

			 SOT23
SERIES PAIR	COMMON CATHODE	COMMON ANODE	
Device Type: BAS70-04	Device Type: BAS70-05	Device Type: BAS70-06	
Partmarking Detail: 2Z	Partmarking Detail: 2Z5	Partmarking Detail: 1Z	

ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Power Dissipation at $T_{amb}=25^{\circ}C$	P_{tot}	330	mW
Operating and Storage Temperature Range	$T_j:T_{stg}$	-55 to +150	$^{\circ}C$

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}C$ unless otherwise stated).

PARAMETER	SYMBOL	MIN.	MAX.	UNIT	CONDITIONS.
Breakdown Voltage	V_{BR}	70		V	$I_R=10\mu A$
Reverse Leakage Current	I_R		200	nA	$V_R=50V$
Forward Voltage	V_F		410	mV	$I_F=1mA$
Forward Current	I_F	15		mA	$V_F=1V$
Capacitance	C_T		2.0	pF	$f=1MHz, V_R=0$
Effective Minority Lifetime (1)	τ		100	ps	$f=54MHz, I_{pk}= 20mA$ (Krakauer Test Method)

(1) Sample Test

For typical characteristics graphs see ZC2800E datasheet.