

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)  
[1996391](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Extract from the online catalog

## PC 6-16/ 9-G1-10,16

Order No.: 1996391

The figure shows a 5-pos. version of the product



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1996391>

Header, Nominal current: 76 A, Nom. voltage: 1000 V, Pitch: 10.16 mm, Number of positions: 9, Color: green, Assembly: Soldering

### Commercial data

EAN	4046356038133
Pack	50 pcs.
Customs tariff	85366990
Weight/Piece	0.03643 KG
Catalog page information	Page 420 (CC-2009)

### Product notes

WEEE/RoHS-compliant since:  
04/15/2004



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### Dimensions / positions

Length	34 mm
Height	13.4 mm
Pitch	10.16 mm
Dimension a	81.28 mm
Number of positions	9

PC 6-16/ 9-G1-10,16 Order No.: 1996391

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1996391>

Pin dimensions	1 x 1.2 mm
Pin spacing	10.16 mm
Hole diameter	1.7 mm

**Technical data**

Insulating material group	I
Rated surge voltage (III/3)	8 kV
Rated surge voltage (III/2)	8 kV
Rated surge voltage (II/2)	6 kV
Rated voltage (III/2)	1000 V
Rated voltage (II/2)	1000 V
Connection in acc. with standard	EN-VDE
Nominal current $I_N$	76 A (41 A in combination with PC 6 plug)
Nominal voltage $U_N$	1000 V
Maximum load current	76 A (41 A in combination with PC 6 plug)
Insulating material	PA
Inflammability class acc. to UL 94	V0

**Certificates / Approvals**



Certification CB, CCA, CUL, SEV, UL

**CUL**

Nominal voltage $U_N$	600 V
Nominal current $I_N$	5 A

**UL**

Nominal voltage $U_N$	600 V
Nominal current $I_N$	5 A

PC 6-16/ 9-G1-10,16 Order No.: 1996391

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1996391>

**Accessories**

Item	Designation	Description
------	-------------	-------------

**General**


1970016	CS-IPC 16/ 6	Coding pin, serves to ensure correct polarization on the PCB during manual mounting
---------	--------------	---

**Plug/Adapter**


1600027	CP-HCC 4	Coding profile, Color: red
---------	----------	----------------------------

**Diagrams/Drawings**

Drilling plan/solder pad geometry



Dimensioned drawing



PC 6-16/ 9-G1-10,16 Order No.: 1996391

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1996391>

---

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2010 Phoenix Contact  
Technical modifications reserved;