

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Mallory Sonalert Products](#)

[MAS800SQ](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

| | | |
|---|----------|-----------------|
| MALLORY Mallory Sonalert Products Inc. | Part # | MAS800SQ |
| | Revision | A |

Sales Outline Drawing

Specifications:

| | |
|----------------------------------|--|
| Oscillation Frequency (Hz) | 2700 ± 500 |
| Operating Voltage (Vdc) | 9 ~ 12 |
| Current Consumption Max. (mA) | 50 @ 12Vdc |
| Sound Pressure Level (dB/min) | 103 @ 10cm @ 12 Vdc |
| Tone/Pulse Rate | Constant |
| Operating Temperature (°C) | -20 ~ +90 |
| Storage Temperature (°C) | -30 ~ +100 |
| Lead Pin | Tin Plated Brass |
| Housing | ABS 777D UL94HB Plastic resin (Color: Gray) |
| Weight (Grams) | 50.4 |
| Condition by wave soldering (°C) | 245 ±5 / 3±0.5 sec |
| Condition by hand soldering (°C) | 350 ±20 / within 5 sec |
| Options | For other options contact factory |

RoHS Compliant

Dimensions: (units: mm)

