

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Mallory Sonalert Products](#)

[MCP320Q](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

| | |
|---|-----------------------|
| MALLORY Mallory Sonalert Products Inc. | Part # MCP320Q |
| Sales Outline Drawing | Revision A |

Specifications:

| | |
|----------------------------------|---|
| Oscillation Frequency (Hz) | 3150 ± 500 |
| Operating Voltage (Vdc) | 3 ~ 20 |
| Rated Voltage (Vdc) | 12 |
| Current Consumption Max. (mA) | 3 ~ 25 |
| Sound Pressure Level (dB/min) | 55 at 2feet at 3 Vdc 74 at 2ft at 20 Vdc |
| Tone/Pulse Rate | Constant |
| Operating Temperature (°C) | -20 ~ +90 |
| Storage Temperature (°C) | -30 ~ +100 |
| Lead Pin | Tin Plated Brass |
| Housing | PC UL-94V2 UL94HB plastic resin (Color: Black) |
| Weight (Grams) | 10 |
| Condition by wave soldering (°C) | 245 ±5 / 3±0.5 sec |
| Condition by hand soldering (°C) | 350 ±20 / within 5 sec |
| Options | For other options contact factory |

Dimensions: (units: mm)

ROHS Compliant

