Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

<u>Fairchild Semiconductor</u> <u>D45H2A</u>

For any questions, you can email us directly: sales@integrated-circuit.com



Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com



D45H2A

PNP Power Amplifier

- This device is designed for power amplifier, regulator and switching circuits where speed is important.
- · Sourced from process 5Q.



1. Base 2. Collector 3. Emitter

Rev. A, February 2002

Absolute Maximum Ratings T_C=25°C unless otherwise noted

Symbol	Parameter	Value	Units	
V _{CEO}	Collector-Emitter Voltage	30	V	
I _C	Collector Current - Continuous	8.0	Α	
T _J , T _{STG}	Operating and Storage Junction Temperature Range	- 55 ~ 150	°C	

Electrical Characteristics T_C=25°C unless otherwise noted

Symbol	Parameter	Test Condition	Min.	Тур.	Max.	Units		
Off Charact	Off Characteristics							
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage	I _C = 100mA, IB = 0	30			V		
I _{CBO}	Collector Cut-off Current	V _{CB} = 60V, IE = 0			10	μΑ		
I _{EBO}	Emitter Cut-off Current	V _{EB} = 5V, IC = 0			100	μΑ		
On Characteristics								
h _{FE}	DC Current Gain	$V_{CE} = 5V, I_{C} = 8A$ $V_{CE} = 5V, I_{C} = 10A$ $V_{CE} = 5V, I_{C} = 12A$	100 80 65					
V _{CE} (sat)	Collector-Emitter Saturation Voltage	$I_C = 8A, I_B = 0.4A$			1	V		
V _{BE} (sat)	Base-Emitter Saturation Voltage	$I_C = 8A, I_B = 0.8A$			1.5	V		
Small Signal Characteristics								
f _T	Current Gain Bandwidth Product	$V_{CE} = 10V, I_{C} = 500mA$	25			MHz		


Thermal Characteristics TA=25°C unless otherwise noted

Symbol	Parameter	Max.	Units
P _D	Total Device Dissipation	60	W
	Derate above 25°C	480	mW/°C
$R_{\theta JC}$	Thermal Resistance, Junction to Case 2.1		°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	62.5	°C/W

©2002 Fairchild Semiconductor Corporation

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com





Dimensions in Millimeters

Distributor of Fairchild Semiconductor: Excellent Integrated System Limited Datasheet of D45H2A - TRANS PNP 30V 8A TO-220

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

 $\mathsf{FAST}^{\mathbb{R}}$ $ACEx^{TM}$ OPTOLOGIC™ SMART START™ VCX™ $FASTr^{TM}$ Bottomless™ OPTOPLANAR™ STAR*POWER™ $\mathsf{CoolFET}^{\mathsf{TM}}$ FRFET™ PACMAN™ Stealth™ CROSSVOLT™ РОРТМ SuperSOT™-3 GlobalOptoisolator™ DenseTrench™ $\mathsf{GTO^{\mathsf{TM}}}$ Power247™ SuperSOT™-6 $\mathsf{PowerTrench}^{\texttt{®}}$ DOME™ HiSeC™ SuperSOT™-8 EcoSPARK™ ISOPLANAR™ QFET™ SyncFET™ QS^{TM} E²CMOS™ TruTranslation™ LittleFET™ EnSigna™ $\mathsf{MicroFET^{\scriptscriptstyle\mathsf{TM}}}$ TinyLogic™ QT Optoelectronics™ FACT™ MicroPak™ Quiet Series™ UHC™ $\mathsf{UltraFET}^{\mathbb{R}}$ FACT Quiet Series™ MICROWIRE™ SLIENT SWITCHER®

STAR*POWER is used under license

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.

©2002 Fairchild Semiconductor Corporation Rev. H4